

RELIABLE & EFFICIENT TRANSAXLES

SPEND LESS TIME MOWING & MORE TIME RELAXING



PROUDLY
DESIGNED & ASSEMBLED
IN THE

USA



SUPERIOR PERFORMANCE

- Maintenance-free design for ease of ownership
- Unmatched maneuverability in tight spaces
- Reliable & quiet performance each & every time

SPECIFICATIONS	ZT-1800	ZT-2200 (EZT)	ZT-2800
Pump Displacement	0.37 in ³ /rev [6 cc/rev]	0.61 in ³ /rev [10 cc/rev]	0.61 in ³ /rev [10 cc/rev]
Motor Displacement	0.61 in ³ /rev [10 cc/rev]	0.61 in ³ /rev [10 cc/rev]	0.97 in ³ /rev [16 cc/rev]
Input Speeds			
Max Hi-idle (No Load)	3000 rpm	3000 rpm	3000 rpm
Min (Loaded)	1800 rpm	1800 rpm	1800 rpm
Output Torque	up to 100 lb-ft [up to 136 Nm]	up to 215 lb-ft [up to 291 Nm]	up to 300 lb-ft [up to 406 Nm]
Speed	up to 5 mph [up to 8 kph]	up to 7 mph [up to 11 kph]	up to 8 mph [up to 12 kph]
Gross Vehicle Weight	up to 667 lbs [up to 302 kg]	up to 900 lbs [up to 408 kg]	up to 1000 lbs [up to 453 kg]
Axle Shaft Diameter	0.75 in [19.05 mm]	1.0 in [25.4 mm]	1.0 in [25.4 mm]
Axle Shaft Options	DD	Two Flats 4-bolt Flange	Tapered 4-bolt Flange 5-bolt Flange
Weight of Unit	18 lbs [8.2 kg]	29 lbs [13 kg]	32 lbs [14.5 kg]

BEST IN CLASS

Hydro-Gear sets the standard for reliable, hard-working transaxles.

Our transaxles are built with high-quality components designed for optimum performance.

Experience the same comfort, control, and durability professionals turn to every day.

